



Intellifocus™ technology to scan items in hand or across the room. Both options deliver split-second first time capture of virtually every barcode, regardless of condition.

**Comprehensive accessories for every job**

This accessory family offers it all — charging and Ethernet cradles for the desktop and backroom, accessories for in-vehicle use, a trigger handle for intensive scanning tasks, an RFID adapter and an adapter cup for backwards compatibility with existing TC5x multi-slot ShareCradles and more.

**Solutions that define a new age of mobility****Calculate accurate parcel dimensions — and shipping charges**

Zebra Dimensioning™ Certified Mobile Parcel<sup>1</sup> is an industry-first solution that utilizes the integrated Time of Flight sensor to collect accurate 'legal for trade' parcel dimensions in just seconds, with the simple press of a button. Pricing is accurate and workers are more productive — no need to manually measure boxes.

**Create a mobile-driven workstation**

Just drop the TC53/TC58 into a Workstation cradle<sup>1</sup> to connect to a monitor, keyboard, mouse, printer and more, eliminating the need to purchase and manage separate fixed workstations.

**Create a complete hybrid Point-of-Sale (POS)**

Drop the TC53/TC58 into the Workstation Point-of-Sale cradle<sup>1</sup> to connect to everything needed to create a complete POS — such as a large display, scanner, receipt printer, payment terminal, keyboard and mouse.

**Add lightning-fast RFID**

Take inventory in record time with the standard range RFD40 and standard or extended range RFD90 Ultra-Rugged UHF RFID sleds. These sleds read an impressive 1,300 tags per second. Connect the sleds via a Bluetooth, NFC or Zebra's eConnex™ adapter. And Wi-Fi 6E enables easy over-the-air management of the mobile computers and their attached sleds.

**Add two-way radio capabilities**

Keep workers everywhere connected with the press of a button. Inside your facility, optional Push-to-Talk (PTT) Express enables instant PTT walkie-talkie style calls over the Wi-Fi network, right out of the box. Out in the field, optional PTT Pro enables PTT calling and secure messaging over the cellular network through an easy-to-

deploy cost-effective subscription service.

**Add PBX handset functionality**

Add fully-featured PBX handset functionality with Zebra's Workforce Connect Voice. The need to purchase and manage additional voice-enabled devices is eliminated. And a custom interface makes it easy to execute even the most complex telephony features.

**Drive workforce productivity and device value to a new level with Mobility DNA****Simplify device integration**

Create rich apps that take full advantage of your device's capabilities with Enterprise Mobility Management Tool Kit. Build feature-rich web applications with Enterprise Browser. And easily capture and integrate barcode data into your apps without writing any code with DataWedge API.

**Increase device security**

Keep your devices secure every day they are in service with LifeGuard™ for Android™<sup>2</sup>. And restrict apps and device features with Enterprise Home Screen.

**Deploy devices quickly and easily**

Let your devices provision themselves right out of the box with Zebra Zero-Touch. Stage a handful or thousands of devices with a scan of a barcode or tap on an NFC tag with StageNow.

**Make device management simple and easy**

Locate missing devices quickly and easily with Device Tracker — and with the BLE battery, you can find devices even if they are turned off or the battery is dead. Get dependably superior Wi-Fi connections with Wireless Fusion. Control which Google Mobile Services are active on your devices with GMS Restricted Mode. Test major device systems to eliminate unnecessary trips to the repair depot with Device Diagnostics.

**Increase on-the-job productivity**

Easily manage Bluetooth accessories with Device Central. Convert 'green' screens to intuitive all-touch modern screens with All-touch Terminal Emulation. Give workers a keyboard designed for your data with Enterprise Keyboard. Capture only the barcodes you want with Simulscan. Capture standardized data such as drivers licenses, license plates with OCR Wedge. And more.

# Specifications

| Physical Characteristics    |  |
|-----------------------------|--|
| <b>Dimensions</b>           | 6.48 in. L x 3.04 in. W x 0.66 in. H<br>164.8 mm L x 77.35 mm W x 16.75 mm H   |
| <b>Weight</b>               | 10.3 oz./293 g with standard battery   |
| <b>Display</b>              | 6.0 in. Full High Definition; 1080x 2160; LED back-light; 600 NITS; optically bonded to touch panel  |
| <b>Imager Window</b>        | Corning® Gorilla® Glass 5  |
| <b>Touch Panel</b>          | Multi-mode capacitive touch with bare or gloved fingertip input or conductive stylus (sold separately), Corning Gorilla Glass; water droplet rejection; fingerprint resistant anti-smudge coating  |
| <b>Power</b>                | Rechargeable Li-Ion, PowerPrecision+ for real-time battery metrics; 17.71 Watt hours; Standard capacity: 4400 mAh; Extended capacity: 6600 mAh; BLE battery: 4400 mAh; Qi compatible Wireless charge battery: 4400 mAh; fast charging Warm Swap battery mode (standard SKUs); Hot Swap battery mode (premium SKUs)             |
| <b>Expansion Slot</b>       | User accessible microSD card supports up to 2 TB   |
| <b>SIM</b>                  | <b>TC58 only:</b> 1 nano SIM; 1 eSIM   |
| <b>Network Connections</b>  | <b>TC53:</b> WLAN, WPAN (Bluetooth)<br><b>TC58 only:</b> WWAN 5G   |
| <b>Notifications</b>        | Audible tone; multi-color LEDs; haptic feedback  |
| <b>Keypad</b>               | On-screen keypad and enterprise keyboard   |
| <b>Voice and Audio</b>      | Three microphones with noise cancellation; vibrate alert; dual speakers for loudness; Bluetooth wireless headset support; high quality speaker phone; PTT headset (3.5 mm and Zebra USB-C) support; cellular circuit switch voice; HD voice; Super-wideband (SWB) and Fullband (FB) audio; 3.5 mm audio jack only on WLAN SKUs |
| <b>Buttons</b>              | Programmable buttons for maximum flexibility: dual dedicated scan buttons, dedicated push-to-talk button, volume up/down buttons and trigger button of trigger handle via Back I/O.  |
| <b>Interface Ports</b>      | USB 2.0 (Back I/O - Host Only), USB 3.0 (Bottom Type C) - Super Speed (Host and Client)  |
| Performance Characteristics |  |
| <b>CPU</b>                  | Qualcomm 6490 octa-core, 2.7 GHz   |
| <b>Operating System</b>     | Android 11; upgradeable to Android 14  |
| <b>Memory</b>               | 4GB RAM/64GB UFS Flash; 8GB RAM/64GB UFS Flash; 8GB RAM/128GB UFS Flash  |
| <b>Security</b>             | FIPS 140-2 Validated (ISO 19790) and Common Criteria certified (ISO 15408); FIPS 140-2 cryptography can be enabled on select configurations through a custom SKU request; Supports Secure Boot and Verified Boot.  |
| User Environment            |  |
| <b>Operating Temp.</b>      | -4°F to 122°F/-20°C to 50°C  |
| <b>Storage Temp.</b>        | -40°F to 158°F/-40°C to 70°C   |
| <b>Humidity</b>             | 5% to 95% non-condensing   |
| <b>Sealing</b>              | IP68 and IP65 with battery per applicable IEC sealing specifications   |

| <b>Drop Specifications</b>                           | Multiple 6 ft./1.8 m drops to concrete over operating temp (-20°C to 50°C/-4°F to 122°F) with protective boot per MIL STD 810H; Multiple 5 ft./1.5 m drops to tile over concrete (-10°C to 50°C/14°F to 122°F) per MIL STD 810H   |
|--|---|
| <b>Tumble Specification</b>                          | 1000 1.6 ft./0.5 m tumbles at room temperature without protective boot, meets or exceeds IEC tumble specification; 1000 3.2 ft./1.0 m tumbles at room temperature with protective boot, meets or exceeds IEC tumble specification   |
| <b>Electrostatic Discharge (ESD)</b>                 | +/- 15 kV air discharge; +/- 8 kV direct discharge; +/- 8 kV indirect discharge   |
| General Certifications                               |   |
| TAA compliant; ARCore Google certification sustained |   |
| Automated Interactive Sensor Technology (IST)        |   |
| <b>Light Sensor</b>                                  | Adjusts display backlight brightness  |
| <b>Magnetometer</b>                                  | eCompass to detect direction and orientation (not available in the base LAN model)  |
| <b>Motion Sensor</b>                                 | 3-axis accelerometer with MEMS Gyro   |
| <b>Pressure Sensor</b>                               | Detects altitude information for locating   |
| <b>Proximity Sensor</b>                              | Disables display output and touch input when placed against head during a call  |
| <b>Gyro</b>  | Senses linear orientation   |
| Data Capture   |   |
| <b>Scanning</b>                                      | SE55 1D/2D Advanced Range Scan Engine with IntelliFocus™ technology; SE4720 1D/2D Scan Engine   |
| <b>Camera</b>  | Front—8 MP; Rear—16 MP autofocus; flash LED generates balanced white light; supports Torch mode + HDR (standard); Optical Image Stabilization (OIS) (premium SKUs only), Time of Flight (ToF) Sensor (premium SKUs only)  |
| <b>NFC</b>   | ISO 14443 Type A and B; FeliCa and ISO 15693 cards; Card Emulation via Host; Contactless payment support, ECP1.0 and ECP2.0 polling support, Apple VAS certified  |
| Wireless WAN, Data and Voice Communications (TC58)   |   |
| <b>GPS</b>   | GPS, GLONASS, Galileo, Beidou, QZSS Dual-Band GNSS — concurrent L1/G1/E1/B1 (GPS/QZSS, GLO, GAL, BeiDou) + L5/E5a/BDSB2a (GPS/QZSS, GAL, BeiDou); a-GPS; supports XTRA  |
| <b>Multimedia</b>                                    | Wi-Fi Multimedia™ (WMM) and WMM-PS; TSPEC   |
| <b>Radio Frequency Band</b>                          | <b>North America: 5G FR1:</b> n2/5/7/12/13/14/25/26/29/38/41/48/66/71/77/78; <b>4G:</b> B2/4/5/7/12/13/14/17/25/26/29/38/41/48/66/71; <b>3G:</b> B2/4/5; <b>2G:</b> 850/1900<br><b>Rest of World: 5G FR1:</b> n1/2/3/5/7/8/20/28/38/40/41/66/71/77/78; <b>4G:</b> B1/2/3/4/5/7/8/17/20/28/38/39/40/41/42/43/66/71; <b>3G:</b> 1/2/3/4/5/8; <b>2G:</b> 850/900/1800/1900<br><b>China/Japan: 5G FR1:</b> n1/3/5/8/38/40/41/77/78/79; <b>4G:</b> B1/3/5/7/8/19/34/38/39/40/41/42; <b>3G:</b> B1/5/8/19; <b>2G:</b> 850/900/1800<br><b>Supports private networking (LTE/5G)</b> |
| Wireless LAN   |   |
| <b>Radio</b>   | IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc/ax; 2x2 MU-MIMO; Wi-Fi™ 6E (801.11ax); Wi-Fi certified; Wi-Fi™ 6E Certified; Dual Band Simultaneous; IPv4, IPv6   |

## Markets and Applications

### Retail Associates

- Price/inventory checks
- Item locator
- Line busting/Mobile Point of Sale
- Assisted selling
- Task management
- Front of store replenishment
- Price management
- Inventory/cycle counts

### Retail Managers

- Workforce mgmt
- Planogram mgmt
- Promotion compliance
- Merchandising
- Back of store management

### Field Service Technicians

- Asset mgmt
- Parts inventory
- Invoicing/Mobile Point of Sale
- Scheduling

### Postal Carriers/Courier Drivers

- Proof of delivery/condition
- Asset mgmt
- Invoicing/Mobile Point of Sale
- Location services

## PRODUCT SPEC SHEET

### TC53/TC58 MOBILE COMPUTERS

|                                |   |
|--------------------------------|---|
| <b>Data Rates</b>              | <b>5GHz:</b> 802.11a/n/ac/ax—20MHz, 40MHz, 80MHz, 160MHz - up to 2402 Mbps<br><b>2.4GHz:</b> 802.11b/g/n/ax—20MHz up to 286.8 Mbps<br><b>6GHz:</b> 802.11ax - 20MHz, 40MHz, 80MHz, 160MHz - up to 2402 Mbps   |
| <b>Operating Channels</b>      | <b>Channel 1-13</b> (2401-2483 MHz):1,2,3,4,5,6,7,8,9,10,11,12,13; <b>Channel 36-165</b> (5150-5850 MHz): 36,40, 44,48,52,56,60,64,100,104,108,112,116,120,124, 128, 132,136,140,144,149,153,157,161,165; <b>Channel 1-233</b> (5925-7125 MHz); <b>Channel Bandwidth:</b> 20/40/80/160 MHz; Actual operating channels/frequencies and bandwidths depend on regulatory rules and certification agency. |
| <b>Security and Encryption</b> | WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise (AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2); EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, LEAP, EAP-PWD); WWAN device only — EAP-SIM, EAP-AKA; WPA3 Enterprise 192-bit mode (GCMP256) — EAP-TLS; Enhanced Open (OWE)   |
| <b>Certifications</b>          | <b>Wi-Fi Alliance Certifications:</b> Wi-Fi CERTIFIED n; Wi-Fi CERTIFIED ac; Wi-Fi CERTIFIED 6; Wi-Fi Enhanced Open; WPA2-Personal; WPA2-Enterprise; WPA3-Personal; WPA3-Enterprise (includes 192-bit mode); Protected Management Frames; Wi-Fi Agile Multiband; WMM; WMM-Power Save; WMM-Admission Control; Voice-Enterprise; Wi-Fi Direct; QoS Management; OCE                                      |
| <b>Fast Roam</b>               | PMKID caching; Cisco CCKM; 802.11r; OKC   |

#### Wireless PAN

|                  |  |
|------------------|--|
| <b>Bluetooth</b> | Class 2, Bluetooth v5.2; secondary Bluetooth Low Energy (BLE) for beaconing within BLE battery |
|------------------|--|

#### Environmental Compliance

RoHS Directive 2011/65/EU; RoHS Amendment (EU) 2015/863; (EN IEC 63000:2018 Standard); For a complete list of product and materials compliance, please visit [www.zebra.com/environment](http://www.zebra.com/environment)

#### Warranty

Subject to the terms of Zebra's hardware warranty statement, the TC53/TC58 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit: [www.zebra.com/warranty](http://www.zebra.com/warranty)

#### Recommended Services

Zebra OneCare™ Essential and Select support services; Zebra Visibility Services — VisibilityIQ™ Foresight; For information on Zebra services, please visit [www.zebra.com/services](http://www.zebra.com/services)

#### Footnotes

1. Workstation cradles and Certified Mobile Parcel available in 2H 2022
2. LifeGuard for Android is included with every Zebra OneCare Support agreement. Some features are available through a supported EMM. Specifications subject to change without notice. For details related to Common Criteria support, please visit: [www.zebra.com/commoncriteria](http://www.zebra.com/commoncriteria)

#### Mobility DNA

For information on Mobility DNA, visit [www.zebra.com/mobilitydna](http://www.zebra.com/mobilitydna). Mobility DNA features vary by model; a support contract may be required. To learn what solutions are supported, visit: <https://developer.zebra.com/mobilitydna>



704-983-1495

questions@scanonline.com

<http://www.scanonline.com>

236 Market St. #210, Locust, North Carolina, 28097, United States



ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. Android is a trademark of Google LLC. All other trademarks are the property of their respective owners. ©2022 Zebra Technologies Corp. and/or its affiliates. 07/13/2022